



Biowave 3+ Color Touch

Spectrophotometers

The Biowave 3+ Color Touch is truly an all-encompassing Life Sciences Spectrophotometer.

From the most basic cell density or single wavelength reading, to low volume molecular quantification, this is the most versatile single beam UV/Visible instrument on the market.

This compact and robust instrument is perfect for most Life Science laboratories, from undergraduate teaching to biotech and R&D, the Biowave 3+ CT can cover the full spectrum of needs.

Features & Benefits

- Wavelength Range: 190 to 1100 nm
- Fast and easy to use wavelength scanning, kinetics, single or multiple wavelength reading, standard curve and absorbance ratio capability
- Pre-loaded Life Science Methods:
 - Nucleic Acid quantification
 - Protein applications (Bradford, Lowry, Biuret, BSA)
 - Nucleic Acid and Protein fluorescent dyes
 - OD 600 Microbial growth
 - Tm calculation
- 2 year warranty

Technical Specifications

Technical	
Wavelength Range	190 to 1100 nm
Monochromator	Flat grating
Wavelength Calibration	Automatic upon switch on
Beam Height	15 mm
Spectral Bandwidth	3 nm
Wavelength Accuracy	±2 nm
Wavelength Reproducibility	±1 nm
Light Sources	Xenon flash lamp
Detector	Twin CMOS array
Photometric Range	-0.300 to 2.500 A, 0.3 to 199 %T
Photometric Linearity	±1.3 % or ±0.008 A whichever is greater at 546 nm
Photometric Reproducibility	±0.002 A to 0.5 A at 546 nm
Stray Light	<0.5 %T 340 nm
Stability	±0.01 A/h at 340 nm
Noise	±0.005 peak to peak ±0.002 RMS

Technical Specifications

Software	
General Laboratory: Single wavelength, Multi wavelength, Concentration, Standard curve/ Wavelength scanning, Kinetics Absorbance ratio	Life Science Laboratory: Nucleic Acid UV quantification, Tm calculation, Protein UV quantification, Protein colorimetry; BSA, Bradford, Lowry and Biuret, Fluorescent label quantification, OD600 microbial culture quantification
Digital Output	USB flash drive, PC via PVC software, Optional: Wireless
Data Export	USB flash drive: .tsv, native PVC format PC via PVC: .csv, .emf, .xlsx, .xls, .rtf, .tsv, native PVC format
Method Storage	90 with PIN number protection
Graphical Display	Color touch screen, zoom and track function
Sample ID	Yes
Languages	English, German, French, Spanish, Italian, Japanese, Chinese
Dimensions	260 × 390 × 100 mm
Weight	3.00 kg

Ordering Info

Order #	Product
80-3007-57	WPA Biowave 3+ CT
80-3007-58	WPA Biowave 3+ CT with Printer
80-3007-59	WPA Biowave 3+ CT Wireless
80-3007-60	WPA Biowave 3+ CT Wireless with Printer



Biochrom Ltd.
Unit 7, Enterprise Zone 3970
Cambridge Research Park,
Cambridge, CB25 9PE, UK

Sales: sales@biochrom-us.com

Technical Support:
enquiries@biochrom.co.uk

Web: www.biochrom.co.uk

United Kingdom:
Tel: +44 (0) 1223 423 7233

Americas:
Tel: +1 800 272 2775